

RESIDENTIAL HVAC DUCT DESIGN GUIDE

Latest Edition

Residential HVAC Duct Design Guide

Designing an efficient and effective HVAC duct system is crucial for ensuring optimal comfort, energy efficiency, and indoor air quality in residential properties. A well-planned duct design minimizes airflow issues, reduces energy costs, and enhances overall system performance. This comprehensive residential HVAC duct design guide provides homeowners, contractors, and HVAC professionals with essential insights and best practices to create a duct system tailored to the unique needs of a home.

Understanding the Basics of HVAC Duct Systems

Before diving into design specifics, it's important to grasp the fundamental components and functions of residential duct systems.

What Is an HVAC Duct System?

An HVAC duct system is a network of passages that distribute heated or cooled air throughout a residence. It connects the furnace or air handler to various vents and registers placed in different rooms.

Key Components of Duct Systems

- **Main ducts:** Large trunks that run from the furnace or air handler to branch ducts.
- **Branch ducts:** Smaller ducts that extend from the main duct to individual rooms.
- **Vents and registers:** The outlets that deliver conditioned air into rooms.
- **Diffusers and grilles:** Coverings that control airflow and aesthetics.

Essential Principles of Duct Design

Effective duct design balances airflow, minimizes energy loss, and ensures even distribution of air.

Airflow and Velocity

Proper airflow ensures consistent temperature control and comfort. Typical airflow rates are:

- For heating or cooling, approximately 400?600 CFM (cubic feet per minute) per ton of cooling capacity.
- Air velocity in supply ducts should be between 600 and 900 feet per minute to prevent noise and pressure loss.

Pressure Loss and Friction

Designing ducts to minimize resistance involves:

- Using appropriately sized ducts to reduce friction.
- Keeping duct runs as straight and smooth as possible.
- Avoiding unnecessary fittings and sharp bends.

Balancing Airflow

Ensuring each room receives the right amount of air involves:

- Calculating required airflow per room based on size and insulation.
- Adjusting dampers and registers to balance airflow.

Steps to Designing a Residential HVAC Duct System

A systematic approach ensures the duct system meets the home's heating and cooling needs.

1. Conduct a Load Calculation

Determine the heating and cooling load for each room using tools like Manual J calculations. This step considers:

- Room size and layout
- Insulation levels
- Window orientation and shading
- Occupancy and appliance heat gains

2. Plan the Duct Layout

Create a layout that minimizes duct length and maximizes efficiency:

- Position the main trunk duct centrally.
- Design branch ducts to serve individual rooms directly.
- Ensure ducts are accessible for maintenance.

3. Select the Right Duct Sizes

Use duct sizing charts or software to determine optimal dimensions:

- Calculate cross-sectional areas based on airflow requirements.
- Balance duct diameters to prevent excessive velocity or pressure loss.

4. Use Proper Materials and Insulation

Select durable, insulating duct materials to prevent energy loss:

- Flexible ducts for tight spaces, rigid ducts for main runs.
- Insulate ducts in unconditioned spaces to prevent heat transfer.

5. Incorporate Dampers and Registers

Install adjustable dampers and properly rated registers:

- Adjust dampers to balance airflow.
- Choose registers that match room size and airflow needs.

Best Practices for Efficient Duct Design

Implementing best practices enhances system performance and longevity.

Minimize Duct Length and Bends

Long and convoluted duct runs increase resistance and energy consumption. Keep runs as direct as possible with gentle bends.

Seal Duct Joints and Connections

Prevent air leaks by sealing all joints with mastic or foil tape, especially at connections and seams.

Insulate Ducts in Unconditioned Spaces

Insulation reduces heat loss or gain, maintains desired temperatures, and improves efficiency.

Use Proper Vent Placement

Vents should be strategically located to promote even airflow, avoid obstructions, and provide comfort.

Regular Maintenance and Inspection

Periodic checks for leaks, blockages, and insulation integrity ensure optimal performance over time.

Common Duct Design Mistakes to Avoid

Being aware of pitfalls helps prevent costly errors:

- Overly small ducts causing high velocity and noise.
- Too many bends and fittings increasing pressure loss.
- Poor sealing leading to air leaks and energy waste.
- Incorrect placement of vents resulting in uneven heating or cooling.
- Ignoring insulation requirements in unconditioned spaces.

Tools and Resources for Duct Design

Leverage specialized tools and resources for precise duct design:

- Manual J and D calculation software
- Duct sizing calculators
- HVAC load calculation manuals
- Professional HVAC design services

Conclusion

A well-designed residential HVAC duct system plays a vital role in achieving comfort, efficiency, and indoor air quality. By understanding the principles of airflow, pressure, and material selection, and following a systematic design process, homeowners and contractors can create duct systems that perform reliably and efficiently for years to come. Regular maintenance, proper sealing, and strategic planning are essential to maintain system performance and energy savings over time.

Whether undertaking a new installation or upgrading an existing system, adhering to this residential HVAC duct design guide ensures optimal results and long-term satisfaction.

Residential HVAC Duct Design Guide

In the realm of residential heating, ventilation, and air conditioning (HVAC), the duct system plays a pivotal role in ensuring optimal comfort, indoor air quality, and energy efficiency. A well-designed duct system not only guarantees even temperature distribution but also minimizes operational costs and noise levels. Given its critical importance, a comprehensive understanding of residential HVAC duct design is essential for contractors, engineers, homeowners, and industry stakeholders aiming to achieve high-performance outcomes. This investigative guide delves into the fundamental principles, best practices, common pitfalls, and emerging trends in residential duct design, providing a thorough resource for informed decision-making.

Understanding the Fundamentals of Residential HVAC Duct Design

At its core, residential HVAC duct design involves planning and implementing a network of air passages that distribute conditioned air throughout a home efficiently and effectively. It encompasses considerations of airflow requirements, material selection, spatial constraints, and system compatibility.

The Importance of Proper Duct Design

A correctly designed duct system ensures:

- Consistent Temperature Control: Even distribution prevents hot or cold spots.
- Energy Efficiency: Minimizes air leakage and reduces system workload.
- Comfort and Air Quality: Maintains appropriate airflow and minimizes contaminants.
- Noise Control: Reduces sound transmission and operational noise.

Conversely, poor duct design can lead to high utility bills, uneven heating or cooling, increased wear on equipment, and compromised indoor air quality.

Key Principles of Residential Duct Design

Effective duct design is grounded in several core principles:

1. Proper Sizing of Ducts

Duct sizing directly impacts airflow and system performance. Overly large ducts cause excessive air

velocity, leading to noise and energy waste, while undersized ducts restrict airflow, resulting in inadequate heating or cooling.

- Methods for Duct Sizing:
 - Manual D Method: Industry-standard calculations based on airflow requirements.
 - Ductulator Tools: Slide rule devices that aid in quick sizing.
 - Software Solutions: Advanced programs for precise design.
- Key Parameters:
 - Airflow rate (CFM - cubic feet per minute)
 - Duct cross-sectional area
 - Velocity (preferably between 600 and 900 ft/min for supply ducts)

2. Maintaining Correct Airflow Velocities

Balancing airflow velocities ensures efficient operation and minimizes noise. Typical recommended velocities are:

- Supply ducts: 600-900 ft/min
- Return ducts: 300-600 ft/min

Exceeding these ranges can cause noise and increased pressure drop.

3. Minimizing Pressure Losses

Design should aim to reduce friction and turbulence within ducts by:

- Using smooth, rigid duct materials
- Avoiding abrupt transitions and sharp bends
- Properly securing ducts to prevent leaks

4. Strategic Duct Layout

A well-planned layout minimizes duct lengths, avoids unnecessary turns, and ensures balanced airflow to all zones.

Components of a Residential HVAC Duct System

A thorough understanding of duct components is crucial to effective design:

Duct Materials

- Flexible ducts (e.g., foil or fiberglass): Easy to install but may be less durable.
- Sheet metal ducts (galvanized steel or aluminum): Durable, smooth interior, better airflow.
- Rigid fiberglass ducts: Insulation properties, reducing thermal losses.

Fittings and Transitions

- Elbows, tees, reducers: Designed to manage airflow paths.
- Dampers: Allow zone-specific airflow control.
- Registers and grilles: Final outlets for conditioned air.

Insulation

Proper insulation of ducts prevents thermal losses and condensation, especially in unconditioned spaces.

Designing for Comfort and Efficiency

Achieving optimal performance involves integrating ergonomic considerations:

Zone Design

Dividing the home into zones allows for targeted heating and cooling, improving comfort and energy savings.

Balancing Airflow

Ensuring each zone receives appropriate airflow prevents disparities. Techniques include:

- Adjusting damper settings
- Using variable speed fans
- Employing zone control systems

Ensuring Accessibility and Maintenance

Design should facilitate easy access for inspection, cleaning, and repairs. Incorporate cleanouts and sufficient clearance.

Common Challenges in Residential Duct Design

Despite best practices, several issues can compromise duct system performance:

1. Duct Leakage

Leaks can account for 20-30% of conditioned air loss, significantly reducing efficiency.

2. Poor Airflow Balance

Uneven distribution causes discomfort and increased energy use.

3. Inadequate Insulation

Leads to thermal losses and condensation issues.

4. Improper Duct Sizing

Results in noise, high energy bills, and system strain.

5. Complexity of Retrofits

Existing homes may pose challenges for duct renovations or replacements, necessitating innovative solutions.

Emerging Trends and Technologies in Residential Duct Design

Advancements are shaping the future of duct system design:

1. Ductless and Mini-Split Systems

Eliminate traditional ductwork, reducing leakage and installation costs.

2. Automated Zoning and Controls

Smart thermostats and zone dampers optimize airflow dynamically.

3. Computational Fluid Dynamics (CFD) Modeling

Allows precise airflow analysis and optimization before installation.

4. Improved Materials

Innovations like aerogel insulation and flexible, high-performance duct materials.

5. Integrating with Building Automation

Enhances system responsiveness and energy management.

Best Practices for Implementing a Residential HVAC Duct Design

Successful duct design involves a collaborative approach:

- Conduct detailed load calculations.
- Use precise duct sizing and layout planning.
- Prioritize airtightness and insulation.
- Incorporate zone control where appropriate.
- Perform system balancing and testing post-installation.
- Regularly inspect and maintain ductwork.

Conclusion

The significance of residential HVAC duct design cannot be overstated. Its impact on comfort, energy consumption, indoor air quality, and system longevity makes it a critical aspect of home climate control. A meticulous, science-based approach grounded in fundamental principles, coupled with knowledge of emerging technologies, empowers professionals and homeowners alike to optimize their HVAC systems. As residential construction and retrofit projects continue to evolve, ongoing education and adherence to best practices in duct design will remain essential for achieving sustainable, efficient, and comfortable indoor environments.

By prioritizing proper sizing, layout, material selection, and maintenance, stakeholders can ensure their HVAC duct systems deliver peak performance well into the future.

Question What are the key considerations in residential HVAC duct design? **Answer** Key considerations include proper sizing for airflow, minimizing duct length and bends to reduce pressure loss, ensuring insulation for energy efficiency, and designing for balanced airflow and ease of maintenance. **Question** How do I determine the correct duct size for my residential HVAC system? **Answer** Duct sizing is typically calculated based on the required airflow (CFM) for each zone, using duct sizing charts or software that account for static pressure and velocity limits, ensuring optimal airflow and

system efficiency. What are common mistakes to avoid in residential duct design? Common mistakes include undersizing or oversizing ducts, improper sealing or insulation, excessive bends and long duct runs, and neglecting proper airflow balancing, all of which can lead to reduced comfort and increased energy costs. How does duct material choice impact residential HVAC performance? Material choice affects durability, insulation properties, and airflow efficiency. Flexible ducts are easy to install but may have higher pressure loss, while rigid ducts like sheet metal provide better airflow and durability but require precise installation. Are there any standards or guidelines for residential HVAC duct design? Yes, standards such as those from the ACCA Manual D provide comprehensive guidelines for duct design, ensuring safe, efficient, and code-compliant HVAC system installations in residential buildings.

Related keywords: residential duct sizing, HVAC duct layout, duct insulation, duct construction standards, airflow optimization, duct material selection, zoning systems, ventilation design, duct leakage correction, energy-efficient duct design

Duct weight calculator

Duct Weight Calculator: Your Essential Tool for Accurate Duct Weight Estimation

Understanding the weight of ductwork is crucial for architects, engineers, contractors, and HVAC professionals. A **duct weight calculator** simplifies this process by providing precise estimations based on various parameters. Whether you're planning a new installation or managing existing infrastructure, knowing the weight of ducts helps in designing support systems, estimating load-bearing requirements, and ensuring safety compliance. In this comprehensive guide, we'll explore the importance of duct weight calculation, how a duct weight calculator works, the factors influencing duct weight, and how to use such tools effectively.

Why Is Duct Weight Calculation Important?

Structural Integrity and Support Planning

Accurately estimating duct weight ensures that building structures can support the load. Overlooking duct weight can lead to insufficient support, risking structural failure or damage over time. Proper support design minimizes vibrations, noise, and wear on the ductwork.

Cost Estimation and Material Planning

Knowing the weight of ducts helps in estimating transportation, handling, and installation costs. It

also assists in selecting appropriate materials and supports, preventing over- or under-spending.

Safety and Compliance

Building codes and safety standards often specify maximum load capacities for ceilings, floors, and supports. Accurate weight calculations ensure compliance and safety for building occupants and maintenance personnel.

Installation and Logistics Management

Heavy ducts require specialized equipment and planning for installation. Knowing the weight beforehand streamlines logistics and reduces onsite delays.

Understanding the Components of Duct Weight

Factors Influencing Duct Weight

Various factors contribute to the overall weight of ductwork, including:

- **Material Type:** Common materials include galvanized steel, aluminum, stainless steel, and fiberglass. Each has different densities and weight characteristics.
- **Cross-Sectional Shape and Size:** Rectangular, round, or oval ducts with different dimensions will weigh differently.
- **Thickness of the Material:** Thicker materials increase weight but offer greater durability and insulation.
- **Additional Components:** Insulation, lining, and accessories add to the total weight.

Basic Calculation Formula

The fundamental formula for calculating duct weight is:

$$\text{Weight} = \text{Volume} \times \text{Material Density}$$

Where:

- Volume is calculated based on duct dimensions.
- Material density depends on the material used.

How Does a Duct Weight Calculator Work?

Input Parameters

Most duct weight calculators require specific inputs to generate an accurate estimate:

- **Duct Shape:** Round, rectangular, or oval.
- **Dimensions:** Diameter for round ducts, width and height for rectangular ducts, or major/minor axes for oval ducts.
- **Material Type:** Steel, aluminum, etc.
- **Material Thickness:** Typically measured in millimeters or inches.
- **Additional Components:** Insulation thickness or lining, if applicable.

Output Results

The calculator processes inputs to provide:

- **Total duct weight:** Usually in kilograms or pounds.
- **Weight per unit length:** Useful for support and handling considerations.
- **Breakdown by components:** Weight of duct material, insulation, and accessories.

Benefits of Using a Duct Weight Calculator

- Saves time compared to manual calculations.
- Reduces errors and inconsistencies.
- Facilitates quick adjustments in design.
- Enhances project planning accuracy.

Materials and Their Impact on Duct Weight

Galvanized Steel

One of the most common duct materials, galvanized steel offers durability and corrosion resistance. Typical densities are around 7.85 g/cm³ (0.284 lb/in³).

Aluminum

Lighter than steel, aluminum ducts are easier to handle and install. Their density is approximately 2.70 g/cm³ (0.098 lb/in³).

Stainless Steel

Stainless steel provides strength and corrosion resistance but is heavier, with a density similar to galvanized steel.

Fiberglass and Plastic

These materials are significantly lighter, making them suitable for specialized applications where weight is a concern.

Practical Steps to Calculate Duct Weight Using a Calculator

Step 1: Gather Duct Specifications

Collect accurate measurements of duct dimensions, material type, and thickness. For example:

- Round duct with a diameter of 600 mm
- Material: Galvanized steel
- Thickness: 1.2 mm

Step 2: Input Data into the Calculator

Enter the gathered specifications into the duct weight calculator. Ensure units are consistent (e.g., all dimensions in meters or inches).

Step 3: Review the Output

Analyze the weight estimates provided. Use this data to plan support structures, transportation, and installation.

Step 4: Adjust Parameters if Needed

Modify dimensions or materials to optimize design, cost, or performance, and recalculate as needed.

Common Applications of Duct Weight Calculators

HVAC System Design and Planning

Engineers use these tools during initial design phases to ensure support systems are adequate and to prevent overloading.

Construction and Installation

Contractors plan logistics and support installation equipment based on weight estimates.

Maintenance and Inspection

Maintenance teams evaluate whether existing supports are sufficient or need reinforcement based on updated weight calculations.

Material Procurement

Procurement departments estimate material quantities and costs, ensuring budgets align with project scope.

Choosing the Right Duct Weight Calculator

Features to Consider

- Compatibility with various duct shapes and materials.
- Ease of use and user interface.
- Ability to handle custom dimensions and insulation layers.
- Export and reporting capabilities.
- Integration with other design tools or CAD software.

Popular Duct Weight Calculators and Tools

- Online calculators provided by HVAC supply companies.
- Specialized engineering software with duct design modules.
- Custom spreadsheets designed for specific project needs.

Conclusion

Accurate duct weight estimation is a vital component of successful HVAC system design, construction, and maintenance. A **duct weight calculator** streamlines this process, providing quick, reliable estimates that inform support design, safety compliance, and project logistics. By understanding the factors influencing duct weight and leveraging the right tools, professionals can optimize their workflows, reduce costs, and ensure the safety and durability of their duct systems. Whether you're planning a new installation or managing existing infrastructure, incorporating precise weight calculations into your workflow is essential for project success.

Additional Tips for Accurate Duct Weight Calculation

- Always double-check measurements for consistency and accuracy.
- Consider environmental factors such as corrosion or insulation effects that may alter weight over time.
- Use reliable and updated material density data for calculations.
- Consult local building codes and standards to ensure compliance.

By integrating these practices with a robust duct weight calculator, you can enhance your project planning, safety, and overall system efficiency.

Duct Weight Calculator: The Essential Tool for Accurate HVAC and Ventilation Planning

When designing or installing ductwork for HVAC systems, ventilation, or industrial applications, understanding the weight of the ducts is crucial. A duct weight calculator serves as an invaluable tool to estimate the weight of various duct materials and sizes, enabling engineers, contractors, and facility managers to plan supports, transportation, and installation with confidence. Accurate weight calculations help prevent structural issues, optimize material usage, and streamline project timelines. In this comprehensive guide, we'll explore everything you need to know about duct weight calculators, from their purpose and how they work to practical tips for use and interpretation.

Why Is Duct Weight Important?

Before delving into the mechanics of a duct weight calculator, it's essential to understand why knowing duct weight matters in real-world applications.

Structural Support and Safety

Heavy ducts require robust support systems. Underestimating weight can lead to inadequate supports, risking structural failure or sagging, which compromises system integrity and safety.

Transportation and Handling

Knowing the weight helps in planning how to transport duct sections, select appropriate lifting equipment, and allocate manpower, reducing accidents and damage during installation.

Cost Estimation and Material Planning

Accurate weight calculations contribute to precise material estimates, freight costs, and overall budget management.

Compliance and Regulations

Some building codes specify maximum load capacities for ceilings, floors, or supports. Accurate duct weight data ensures compliance with these standards.

How Does a Duct Weight Calculator Work?

A duct weight calculator essentially estimates the total weight of a duct based on its dimensions, material type, and thickness. Here's how it works:

- Input of Duct Dimensions
 - Shape: Rectangular or round (circular)
 - Size: Length, width, height, or diameter
- Selection of Material Type

Common duct materials include:

- Galvanized steel
- Aluminum
- Stainless steel
- Flexible duct materials

Each material has specific density values.

- Specification of Material Thickness

Ducts come in various thicknesses, affecting their weight. The calculator uses this data to refine estimates.

- Calculation Process

The calculator applies formulas based on the selected shape and material properties to determine:

- Cross-sectional area
- Volume (area $\times$ length)
- Total weight (volume $\times$ material density)

Step-by-Step Guide to Using a Duct Weight Calculator

Step 1: Determine Duct Dimensions

Measure or obtain specifications for your duct:

- For round ducts, note the diameter and length.
- For rectangular ducts, record width, height, and length.

Step 2: Choose the Material Type

Identify the duct material:

- Galvanized steel
- Aluminum
- Stainless steel
- Flexible duct (note that flexible ducts often have different weight considerations)

Step 3: Input Thickness

Select the gauge or thickness of the duct material. Common gauges for steel and aluminum are available in standard values.

Step 4: Enter Data into the Calculator

Input all the gathered data into the digital calculator or manual formulas.

Step 5: Review the Result

The calculator provides an estimated weight, typically expressed in pounds or kilograms.

Practical Applications and Examples

To illustrate, let's examine a typical scenario:

Example:

A contractor needs to determine the weight of a 10-foot-long galvanized steel round duct with a diameter of 12 inches and a wall thickness of 0.016 inches (16 gauge).

Process:

- Convert dimensions to consistent units (feet to inches if necessary).
- Use formulas or an online calculator to input data.
- The calculator computes the volume of the duct material (including the wall thickness), then multiplies by the density of galvanized steel (~0.283 lb/in³).

Result:

The estimated weight might be approximately 45 pounds for the entire 10-foot section.

This data helps in deciding the support spacing and lifting equipment needed during installation.

Factors Affecting Duct Weight and Calculation Accuracy

While calculators provide estimates, several factors can influence the actual weight:

- Material Density Variations: Manufacturing tolerances can cause slight differences.
- Duct Design Features: Reinforcements, flanges, or insulation add weight.
- Corrosion or Wear: Over time, corrosion may alter the weight slightly.
- Manufacturing Standards: Different standards may specify different wall thicknesses or materials.

Always cross-reference calculator results with manufacturer specifications when possible for critical applications.

Tips for Accurate Duct Weight Calculation

- Use Precise Measurements: Always measure ducts accurately, especially for custom sizes.
- Select Correct Material and Gauge: Confirm material type and thickness from supplier data.
- Account for Additional Components: Include weights of fittings, flanges, and insulation if relevant.
- Utilize Reliable Tools: Use reputable online calculators or detailed formulas for better accuracy.

- Consult Manufacturer Data: When in doubt, refer to manufacturer specifications for exact weights.

Advantages of Using a Duct Weight Calculator

- Efficiency: Quickly generate weight estimates without manual calculations.
- Accuracy: Reduce errors compared to rough estimates.
- Planning: Facilitate better logistical and structural planning.
- Cost Management: Help avoid over- or under-estimating material and support needs.
- Safety: Ensure support systems are designed to handle the actual load.

Conclusion

A duct weight calculator is an indispensable tool for anyone involved in HVAC design, duct manufacturing, or installation projects. By understanding how to accurately estimate duct weights, professionals can optimize support structures, streamline logistics, and ensure safety and compliance. Whether using online digital tools or manual formulas, mastering duct weight calculation empowers you to execute projects with confidence and precision. Remember to always verify your estimates with manufacturer data and consider all additional components to ensure your ductwork setup is both safe and cost-effective.

Question What is a duct weight calculator and how does it work? A duct weight calculator estimates the weight of air ducts based on their dimensions, material type, and thickness, helping engineers determine load requirements and material costs efficiently. **Why is calculating duct weight important in HVAC design?** Calculating duct weight is crucial for ensuring structural support, safety, and proper installation, especially for large or heavy duct systems that may impact building load calculations. **What materials are commonly used in duct weight calculations?** Common materials include galvanized steel, aluminum, stainless steel, and flexible duct materials, each with different densities affecting the overall weight calculations. **Can a duct weight calculator account for different duct shapes?** Yes, most duct weight calculators can handle various shapes like rectangular, round, or oval ducts by inputting specific dimensions for accurate weight estimation. **How accurate are online duct weight calculators?** Online duct weight calculators provide estimates based on standard material densities and dimensions, but actual weights may vary depending on manufacturing tolerances and additional components. **What inputs are required to use a duct weight calculator effectively?** Typically, you need the duct's length, cross-sectional dimensions, material type, and wall thickness to obtain an accurate weight estimate. **How can duct weight calculations influence material selection?** By knowing the weight, designers can choose appropriate materials that meet structural support requirements while optimizing for cost and durability. **Are there mobile apps available for duct weight calculation?** Yes, several HVAC design apps and tools are available for smartphones and tablets that include duct weight calculation features for on-the-go estimation. **How**

does duct weight impact the overall HVAC system design? Duct weight affects structural support needs, material costs, and installation procedures, making accurate calculations essential for safe and efficient HVAC system design. Can a duct weight calculator help prevent installation issues? Absolutely, by accurately estimating duct weight beforehand, installers can ensure proper support and avoid structural problems during and after installation.

Related keywords: duct weight, duct weight calculator online, HVAC duct weight, sheet metal duct weight, duct material weight, duct construction weight, duct weight estimation, duct fabrication weight, duct weight chart, duct weight calculation tool

Read the full article online: [duct weight calculator](#)